



Excellence in Illumination Engineering Software
since 1984



sample banner copyright 2013 Lighting Analysts, Inc.

Photometric Report (Type C)

Filename: L105-30-2200K-T5M.ies

[TEST] 05887

[TESTLAB] A.L.P.-LEXALITE

[ISSUEDATE] 3/14/2017

[MANUFAC] MATECH

[LUMINAIRE] 424 V WITH MATECH D4 LED LIGHT ENGINE WITH SILICONE LENS

Maximum Candela = 1829.97755944729 at 202.5 H 72.5 V

Classification:

Road Classification: Type VS, Short, Semi-Cutoff (deprecated)

Upward Wast Light Ratio: 0.08

Luminaire Efficacy Rating (LER): 107

Indoor Classification: Direct

BUG Rating : B3-U3-G1


Polar Candela Curves:

Vertical Plane Through:

1) 202.5 - 22.5 Horizontal

Horizontal Cone Through:

2) 72.5 Vertical





Excellence in Illumination Engineering Software
since 1984



sample banner copyright 2013 Lighting Analysts, Inc.

Photometric Report (Type C)

Filename: L105-30-2200K-T5M.ies

[TEST] 05887

[TESTLAB] A.L.P.-LEXALITE

[ISSUEDATE] 3/14/2017

[MANUFAC] MATECH

[LUMINAIRE] 424 V WITH MATECH D4 LED LIGHT ENGINE WITH SILICONE LENS

Maximum Candela = 1829.97755944729 at 202.5 H 72.5 V

Classification:

Road Classification: Type VS, Short, Semi-Cutoff (deprecated)

Upward Waste Light Ratio: 0.08

Luminaire Efficacy Rating (LER): 107

Indoor Classification: Direct

BUG Rating : B3-U3-G1

LCS Summary:

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	20.2	0.6	0.6
FM (30-60)	332.3	10.3	10.3
FH (60-80)	1051.6	32.5	32.8
FVH (80-90)	76.6	2.4	2.4
BL (0-30)	19.0	0.6	0.6
BM (30-60)	312.7	9.7	9.7
BH (60-80)	1071.9	33.1	33.4
BVH (80-90)	80.0	2.5	2.5
UL (90-100)	70.6	2.2	2.2
UH (100-180)	175.5	5.4	5.5
Total	3210.4	99.3	100.0
BUG Rating	B3-U3-G1		

