



Excellence in Illumination Engineering Software  
since 1984



sample banner copyright 2013 Lighting Analysts, Inc.

## Photometric Report (Type C)

Filename: L105-30-5000K-T5M.ies

[TEST] 05887

[TESTLAB] A.L.P.-LEXALITE

[ISSUEDATE] 3/14/2017

[MANUFAC] MATECH

[LUMINAIRE] 424 V WITH MATECH D4 LED LIGHT ENGINE WITH  
SILICONE LENS

Maximum Candela = 2221.79755732417 at 202.5 H 72.5 V

### Classification:

Road Classification: Type VS, Short, Semi-Cutoff (deprecated)

Upward Wast Light Ratio: 0.08

Luminaire Efficacy Rating (LER): 130

Indoor Classification: Direct

BUG Rating : B3-U3-G1


### Polar Candela Curves:

Vertical Plane Through:

1) 202.5 - 22.5 Horizontal

Horizontal Cone Through:

2) 72.5 Vertical





Excellence in Illumination Engineering Software  
since 1984



sample banner copyright 2013 Lighting Analysts, Inc.

## Photometric Report (Type C)

Filename: L105-30-5000K-T5M.ies

[TEST] 05887

[TESTLAB] A.L.P.-LEXALITE

[ISSUEDATE] 3/14/2017

[MANUFAC] MATECH

[LUMINAIRE] 424 V WITH MATECH D4 LED LIGHT ENGINE WITH SILICONE LENS

Maximum Candela = 2221.79755732417 at 202.5 H 72.5 V

### Classification:

Road Classification: Type VS, Short, Semi-Cutoff (deprecated)

Upward Waste Light Ratio: 0.08

Luminaire Efficacy Rating (LER): 130

Indoor Classification: Direct

BUG Rating : B3-U3-G1

### LCS Summary:

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	24.5	0.6	0.6
FM (30-60)	403.4	10.3	10.3
FH (60-80)	1276.8	32.8	32.8
FVH (80-90)	93.0	2.4	2.4
BL (0-30)	23.0	0.6	0.6
BM (30-60)	379.6	9.7	9.7
BH (60-80)	1301.4	33.4	33.4
BVH (80-90)	97.2	2.5	2.5
UL (90-100)	85.7	2.2	2.2
UH (100-180)	213.1	5.5	5.5
Total	3897.7	100.0	100.0
BUG Rating	B3-U3-G1		

