



Excellence in Illumination Engineering Software
since 1984



sample banner copyright 2013 Lighting Analysts, Inc.

Photometric Report (Type C)

Filename: L105-80-2200K-T5M.ies

[TEST] 05887

[TESTLAB] A.L.P.-LEXALITE

[ISSUEDATE] 3/14/2017

[MANUFAC] MATECH

[LUMINAIRE] 424 V WITH MATECH D4 LED LIGHT ENGINE WITH SILICONE LENS

Maximum Candela = 4305.56753396988 at 202.5 H 72.5 V

Classification:

Road Classification: Type VS, Short, Semi-Cutoff (deprecated)

Upward Wast Light Ratio: 0.08

Luminaire Efficacy Rating (LER): 97

Indoor Classification: Direct

BUG Rating : B4-U3-G2


Polar Candela Curves:

Vertical Plane Through:

1) 202.5 - 22.5 Horizontal

Horizontal Cone Through:

2) 72.5 Vertical





Excellence in Illumination Engineering Software
since 1984



sample banner copyright 2013 Lighting Analysts, Inc.

Photometric Report (Type C)

Filename: L105-80-2200K-T5M.ies

[TEST] 05887

[TESTLAB] A.L.P.-LEXALITE

[ISSUEDATE] 3/14/2017

[MANUFAC] MATECH

[LUMINAIRE] 424 V WITH MATECH D4 LED LIGHT ENGINE WITH SILICONE LENS

Maximum Candela = 4305.56753396988 at 202.5 H 72.5 V

Classification:

Road Classification: Type VS, Short, Semi-Cutoff (deprecated)

Upward Waste Light Ratio: 0.08

Luminaire Efficacy Rating (LER): 97

Indoor Classification: Direct

BUG Rating : B4-U3-G2

LCS Summary:

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	47.6	0.6	0.6
FM (30-60)	781.8	10.3	10.3
FH (60-80)	2474.3	32.7	32.8
FVH (80-90)	180.3	2.4	2.4
BL (0-30)	44.6	0.6	0.6
BM (30-60)	735.7	9.7	9.7
BH (60-80)	2521.9	33.3	33.4
BVH (80-90)	188.3	2.5	2.5
UL (90-100)	166.1	2.2	2.2
UH (100-180)	413.0	5.5	5.5
Total	7553.6	99.8	100.0
BUG Rating	B4-U3-G2		

